

Genuine Quality.

Durable Trust.





## Antifreeze

9.58001

DT Spare Parts Anti-Freeze 9.58001 is a coolant with an ethyl glycol base that protects the engine and cooling circuit excellently against freezing, rust and overheating. It is suitable for light-metal engines.

The minimum concentration should not go below 35%, which should be particularly considered for operation in summer. It is recommended that the coolant should be changed after 5 years' use, at the latest.

| Mixing table:    | Frost protection until | -19°C | -29°C | -36°C | -38°C |
|------------------|------------------------|-------|-------|-------|-------|
| Antifreeze GW 11 | Vol.%                  | 30    | 40    | 45    | 50    |
| Tap water        | Vol.%                  | 70    | 60    | 55    | 50    |

## **Specifications:**

- ASTM D3306
- ASTM D4656
- ASTM D4958
- BMW GS 94000
- BS 6580
- Chrysler MS-7170
- Cummins 85T8
- Deutz DQC CA-14
- Ford ESD-M97B94-A
- FSD 8704
- Iveco Standard 18-1830
- JASO M325 (Japan)
- KSM 2142
- Lada TTM VAZ 1.97.717-97
- MAN 324 NF
- MB 325.0 & 325.2
- MTU MTL 5048
- NATO S-759
- NFR 15-601
- Opel GME L301
- SAE J1034

- Saab 6901 599
- SAE J1034
- Volvo 128 6083/002
- VW / Audi / Seat / Skoda / Porsche TL 774-C (G11)

Information is subject to change without notice. The vehicle manufacturer's specifications apply respectively. More information can be found on the safety data sheet.

Shop 24/7 here:

partnerportal.dieseltechnic.com